



DESCRIPTION Antistatic high quality acrylic, developed mainly for electronics industry, manufacture and security guards.

DIMENSIONS PER SHEET: 1.24 mts. x 2.45 mts. , 1 mt. x 2 mts.

THICKNESS(mm): 2,5,6,8

ATTRIBUTES	SPECIFICATIONS	TEST RESULTS		J.M
		S1	S2	

DIMENSIONS	Size (mm)	± 1mm		o.k.	o.k.	o.k.
	Thickness	± 0.5mm		o.k.	o.k.	o.k.
PROPERTIES	Surface Resistance	10 ⁶ ~ 10 ⁸ Ω /cm ³		10 ⁷	10 ⁸	o.k.
	Adhesion	Cross hatch		o.k.		o.k.
APPEARANCE	Pin hole particle	2.0mm	< 3EA	1	1	o.k.
	Black spot	1.0mm	< 10EA	2	2	o.k.
	White spot					o.k.
	Bubble	<1.0 mm (not crowded)		o.k.	o.k.	o.k.
	Scratch	10mm	< 2EA	0	0	o.k.
	Color	Based on limit sample		o.k.	o.k.	o.k.
CHEMICALS	IPA (50%) rubbing (10 objetos)	no charge		o.k.	o.k.	





ADVANTAGES

- Electrostatic discharge (ESD)
- Transparent acrylic for better visibility

APPLICATIONS

- Antistatic Trays
- Support for repairing cards
- Divisions
- Security guards

